

90.12.00.4 Citation



No. 90 Citation

- the Citation comes standard with 2" thick back poly
- nominal back height for the Citation is 34"
- rear panel of the No. 90 back is one-piece injection molded, high impact HDPE
- inner upholstery panel is constructed of 5-ply, 7/16" plywood
- back wings are formed from 14 gauge steel
- available in 15 standard plastic colors
- available with an optional lumbar support
- available with tufted cover



No. 12 Universal Seat

- The No. 12 Seat is available in a serpentine spring support component or with an ergonomic substrate and formed poly cushion
- The foundation is injection molded, glass filled polyethylene which is especially strong but not brittle
- The No. 12 Seat passes the 600 lb. static load test and surpasses 300,000 cycles without failure in the ASTM-851-87 Test Method for Self Rising Seat Mechanisms
- Cover utilizes drawstring construction for an unwrinkled appearance and ease of replacement
- Seat pivot is covered to prevent tampering
- Available in full fold, 3/4 fold (standard) or 1/2 fold options
- Available in 15 standard plastic colors
- available with decorative wood veneer or upholstered bottom inserts
- Available with underseat book box

No. 00 Aisle Panel

- "open" aisle end with an attractive seat landing bracket cover
- available for riser or floor mounting
- available with low voltage LED aisle light
- available with cupholder attachment
- available with self-storing writing tablets
- available with four armrest options (comfort curved polymer shown)

No. 4 Chair Platform

- steel standards are constructed from 14 gauge steel and formed into a hexagonal-like column with the seat brackets made from 7 gauge steel, and the formed foot from 12 gauge steel all robotic welded for superior strength
- available in 15 standard powder coat colors
- standards are available floor and riser mount
- available in a variety of floor inclines
- available with four styles of armrests, cupholder attachment or tablet arms