


DAKTRONICS MS-2025 PRODUCT SPECIFICATIONS



This outdoor LED multisport scoreboard displays period time to 99:59, HOME and GUEST scores to 99 and PERIOD to nine. When period time is less than one minute, the scoreboard displays time to 1/10 of a second. Scoreboard shown with optional striping and amber PanaView® digits.

DIMENSIONS	UNCRATED WEIGHT	POWER (120 VAC)*	
3'-6" H x 6'-0" W x 8" D (1.07 m, 1.83 m, 203 mm)	70 lb (32 kg)	Red/Amber Digits	80 Watts, 0.7 Amp
		White Digits	130 Watts, 1.1 Amps

*Scoreboard requires a dedicated circuit. Models with 240 VAC power at half the indicated amperage are also offered (International Use Only).

DIGITS

- All digits are 10" (254 mm) high.
- Select red, amber, or white LED digits.
- Scoreboard features robust weather-sealed digits (see [DD2495646](#)).
- Digits may be dimmed for night viewing.

CAPTIONS

- All captions are 5" (127 mm) high.
- Standard captions are vinyl, applied to the display face.

DISPLAY COLOR

Choose from 150+ colors (from Martin Senour® paint book) at no additional cost.

CONSTRUCTION

Alcoa aluminum alloy 5052 for excellent corrosion resistance

PRODUCT SAFETY APPROVAL

ETL-listed to UL 48, tested to CSA standards, and CE-labeled

OPERATING TEMPERATURES

- Display: -22° to 122° Fahrenheit (-30° to 50° Celsius)
- Console: 32° to 130° Fahrenheit (0° to 54° Celsius)

DAKTRONICS MS-2025 PRODUCT SPECIFICATIONS

CONTROL CONSOLES	CONTROL OPTIONS
All Sport® 1600* (see SL-04352) <i>*May be upgraded to</i> All Sport 5000 (see SL-03991)	Wired (standard): One-pair shielded cable of 22 AWG minimum is required. A cover plate with mounted connector and standard 2" x 4" x 2" (51 mm x 102 mm x 51 mm) outlet box is provided. Connector mates with signal cable from control console. Wireless (optional): 2.4 GHz spread spectrum radio features 64 non-interfering channels and 8 broadcast groups (see SL-04370).
RC-200 (see DD3715714)	Optional wireless handheld controller features 2.4 GHz spread spectrum radio with 64 non-interfering channels and 8-10 hours of operation via internal rechargeable battery.
DAK Score & MX-1 (see DD3888368)	CUSTOMER-SUPPLIED mobile device or tablet with DAK Score app installed communicates via Bluetooth® wireless technology to an MX-1 Interface Box that controls the scoreboard through 2.4 GHz radio or wired connection.

HORN

A vibrating horn, mounted behind the scoreboard face, sounds automatically when period clock counts down to zero or manually as controlled by the operator.

SEGMENT TIMER MODE

The segment timer mode is ideal for keeping practices on schedule. The horn at the end of a segment allows coaches and athletes to focus on the practice and to listen for the horn when it is time to change drills (see [SL-04004](#)).

TIME OF DAY MODE

This scoreboard features a Time of Day (TOD) mode that allows it to act as a clock when the control console is unplugged or off. Refer to the scoreboard installation manual for instructions on how to enable the Time of Day mode.

MOUNTING

Scoreboard is typically mounted on two vertical beams or poles. Hardware to mount scoreboard on two beams is included; hardware for more beams is at additional cost. Standard mounting uses I-beam clamps. Optional mounting method using angle brackets is also offered; maximum beam width is 10" (254 mm) and maximum beam depth is 13" (330 mm). Refer to attached drawings for more information on mounting methods.

SERVICE ACCESS

Digit panels and electronics are serviced from the front of the scoreboard.

OPTIONS & ACCESSORIES

- Scoreboard border striping
- Multiple caption and striping colors (see [DD2101644](#))
- Team name caption in place of HOME
- Reversible HALF and INNING caption panel
- Two 11.125" (283 mm) tall x 1'-1.5" (343 mm) wide logo/sponsor area. Copy is applied to the display face.
- Individual digit protective screens (see [SL-04939](#))
- Protective netting (see [DD2690927](#))
- Optional angle bracket mounting method
- Advertising/identification panels
- Decorative accents
- Electronic message centers and video displays in multiple sizes

GENERAL INFORMATION

Scoreboard provides scoring capabilities for two teams. 100% solid state electronics are housed in an all aluminum cabinet. Scoreboard is shipped in one section. Scoreboard power is to be provided on a dedicated circuit to prevent loss of game information due to failure of another component on the circuit. Specifications and pricing are subject to change without notice.

ADVERTISING/IDENTIFICATION PANELS

Backlit & Non-Backlit Top/Bottom:

- 1'-6" H x 6'-0" W (457 mm, 1.83 m)
- 2'-0" H x 6'-0" W (610 mm, 1.83 m)
- 2'-6" H x 6'-0" W (762 mm, 1.83 m)

Non-Backlit Sides:

- 3'-6" H x 3'-0" W (1.07 m, 914 mm)

For additional non-backlit panel sizes, see [SL-03761](#).

FOR ADDITIONAL INFORMATION

- Installation Specifications: DWG-1173105 (attached)
 - One Ad Panel: DWG-1173106 (attached)
 - Two Ad Panels: DWG-1173107 (attached)
- Standard I-beam Mounting: DWG-1129110 (attached)
- Optional Pole Mounting: DWG-1130246 (attached)
- Component Locations: DWG-1128100 (attached)
- Architectural Specifications: See [DD1745307](#)

ALTERNATE CAPTIONS & SCORING MODES



The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Daktronics, Inc. is under license.

NOTES:

1. FOOTING AND COLUMN SIZES ARE SUGGESTIONS ONLY, PROVIDED TO ASSIST WITH ESTIMATING INSTALLATION COSTS AND ARE NOT INTENDED FOR CONSTRUCTION PURPOSES. THE DESIGN MUST BE CERTIFIED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF THE INSTALLATION BEFORE THEY CAN BE USED FOR FABRICATION OR ERECTION.

2. INTERNATIONAL BUILDING CODE 2012 USED IN DESIGN OF COLUMNS AND FOOTINGS WITH, IMPORTANCE FACTOR=1, Kzt=1.0, Kd=0.85, G=0.85. SEISMIC DESIGN WAS NOT CONSIDERED.

3. FOOTING DIMENSIONS ARE BASED ON ASSUMED SOIL CLASS 4 (ALLOWABLE LATERAL BEARING PRESSURE OF 150 psf).

4. STRUCTURAL STEEL IS GRADE A992 (50 ksi) STEEL. CONCRETE SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2500 psi.

5. THE AVERAGE DISPLAY WEIGHT FOR A LAYOUT CAN NOT EXCEED 8 PSF.


6. DAKTRONICS INC. IS NOT RESPONSIBLE FOR STRUCTURES DESIGNED AND INSTALLED BY OTHERS.

7. LOCAL BUILDING OFFICIALS SHOULD BE CONTACTED TO DETERMINE THE WIND SPEED AND EXPOSURE CATEGORY FOR THE PROPOSED SIGN LOCATION. THE EXPOSURE CATEGORIES B AND C ARE DEFINED AS:

EXPOSURE B - URBAN AND SUBURBAN AREAS, WOODED AREAS, OR OTHER TERRAIN WITH NUMEROUS CLOSELY SPACED OBSTRUCTIONS HAVING THE SIZE OF SINGLE-FAMILY DWELLINGS OR LARGER. THESE CONDITIONS MUST PREVAIL FOR A DISTANCE FROM THE SIGN OF AT LEAST 2,600 ft OR 20 TIMES THE SIGN HEIGHT, WHICHEVER IS GREATER

EXPOSURE C - OPEN TERRAIN WITH SCATTERED OBSTRUCTIONS HAVING HEIGHTS GENERALLY LESS THAN 30 FT. THIS CATEGORY INCLUDES FLAT OPEN COUNTRY, GRASSLANDS, AND ALL WATER SURFACES IN HURRICANE PRONE REGIONS.

8. FOR SPECIFIC PRODUCT DETAILS ON WEIGHT, MOUNTING, ETC. REFER TO THE INDIVIDUAL PRODUCT SPECIFICATION SHEETS.



EXPOSURE B

HEIGHT ABOVE GRADE (A) (FT)	AD PANEL HEIGHT (FT)	COMBINED HEIGHT (B) (FT)		DESIGN WIND VELOCITY			
				115 MPH	130 MPH	150 MPH	170 MPH
10'	NONE	3'-6"	COLUMN	W6X15	W6X15	W6X15	W6X15
			FOOTING	2'-0"x4'-6"	2'-0"x5'-0"	2'-0"x5'-6"	2'-0"x6'-0"
	2'-0"	5'-6"	COLUMN	W6X15	W6X15	W6X15	W6X20
			FOOTING	2'-0"x5'-6"	2'-0"x6'-0"	2'-0"x6'-6"	2'-0"x7'-0"
15'	NONE	3'-6"	COLUMN	W6X15	W6X15	W6X15	W6X20
			FOOTING	2'-0"x5'-0"	2'-0"x5'-6"	2'-0"x6'-0"	2'-0"x6'-6"
	2'-0"	5'-6"	COLUMN	W6X20	W6X20	W6X20	W8X24
			FOOTING	2'-0"x6'-0"	2'-0"x6'-6"	2'-0"x7'-0"	2'-0"x7'-6"

EXPOSURE C


HEIGHT ABOVE GRADE (A) (FT)	AD PANEL HEIGHT (FT)	COMBINED HEIGHT (B) (FT)		DESIGN WIND VELOCITY	
				115 MPH	140 MPH
10'	NONE	3'-6"	COLUMN	W6X15	W6X15
			FOOTING	2'-0"x5'-0"	2'-0"x6'-0"
	2'-0"	5'-6"	COLUMN	W6X15	W6X15
			FOOTING	2'-0"x6'-0"	2'-0"x7'-0"
15'	NONE	3'-6"	COLUMN	W6X15	W6X20
			FOOTING	2'-0"x5'-6"	2'-0"x6'-6"
	2'-0"	5'-6"	COLUMN	W6X20	W8X24
			FOOTING	2'-0"x6'-6"	2'-0"x7'-6"

FOOTING DIMENSIONS = DIAMETER X DEPTH

REV 01	DATE: 01 APR 16	REMOVE MODEL NUMBERS TO MAKE DWG GENERIC	BY: KDD
		THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF DAKTRONICS, INC. OR ITS WHOLLY OWNED SUBSIDIARIES. COPYRIGHT 2016 DAKTRONICS, INC. (USA)	
THIRD ANGLE PROJECTION			
PROJECT: OUTDOOR LED SCOREBOARDS			
TITLE: INSTALLATION SPECS: 3'-6"x6' MODELS, 6' WIDE DISPLAY			
DATE: 15 MAY 14	DIM UNITS: INCHES [MILLIMETERS]	SHEET	REV
SCALE: 1=90	DO NOT SCALE DRAWING		01
DESIGN: TTASCHNER	JOB NO. P1192	FUNC - TYPE - SIZE R - 10 - A	1173105
DRAWN: TTASCHNER			

NOTES:

1. FOOTING AND COLUMN SIZES ARE SUGGESTIONS ONLY, PROVIDED TO ASSIST WITH ESTIMATING INSTALLATION COSTS AND ARE NOT INTENDED FOR CONSTRUCTION PURPOSES. THE DESIGN MUST BE CERTIFIED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF THE INSTALLATION BEFORE THEY CAN BE USED FOR FABRICATION OR ERECTION.
2. INTERNATIONAL BUILDING CODE 2012 USED IN DESIGN OF COLUMNS AND FOOTINGS WITH, IMPORTANCE FACTOR=1, Kzt=1.0, Kd=0.85, G=0.85. SEISMIC DESIGN WAS NOT CONSIDERED.
3. FOOTING DIMENSIONS ARE BASED ON ASSUMED SOIL CLASS 4 (ALLOWABLE LATERAL BEARING PRESSURE OF 150 psf).
4. STRUCTURAL STEEL IS GRADE A992 (50 ksi) STEEL. CONCRETE SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2500 psi.
5. THE AVERAGE DISPLAY WEIGHT FOR A LAYOUT CAN NOT EXCEED 8 PSF.
6. DAKTRONICS INC. IS NOT RESPONSIBLE FOR STRUCTURES DESIGNED AND INSTALLED BY OTHERS.
7. LOCAL BUILDING OFFICIALS SHOULD BE CONTACTED TO DETERMINE THE WIND SPEED AND EXPOSURE CATEGORY FOR THE PROPOSED SIGN LOCATION. THE EXPOSURE CATEGORIES B AND C ARE DEFINED AS:
- EXPOSURE B - URBAN AND SUBURBAN AREAS, WOODED AREAS, OR OTHER TERRAIN WITH NUMEROUS CLOSELY SPACED OBSTRUCTIONS HAVING THE SIZE OF SINGLE-FAMILY DWELLINGS OR LARGER. THESE CONDITIONS MUST PREVAIL FOR A DISTANCE FROM THE SIGN OF AT LEAST 2,600 ft OR 20 TIMES THE SIGN HEIGHT, WHICHEVER IS GREATER
- EXPOSURE C - OPEN TERRAIN WITH SCATTERED OBSTRUCTIONS HAVING HEIGHTS GENERALLY LESS THAN 30 FT. THIS CATEGORY INCLUDES FLAT OPEN COUNTRY, GRASSLANDS, AND ALL WATER SURFACES IN HURRICANE PRONE REGIONS.
8. FOR SPECIFIC PRODUCT DETAILS ON WEIGHT, MOUNTING, ETC. REFER TO THE INDIVIDUAL PRODUCT SPECIFICATION SHEETS.



EXPOSURE B

HEIGHT ABOVE GRADE (A) (FT)	DISPLAY HEIGHT (FT)		DESIGN WIND VELOCITY			
			115 MPH	130 MPH	150 MPH	170 MPH
10'	3'-6"	COLUMN	W6X15	W6X15	W6X15	W6X15
		FOOTING	2'-0"X5'-0"	2'-0"X5'-6"	2'-0"X6'-0"	2'-0"X6'-6"
15'	3'-6"	COLUMN	W6X20	W6X20	W6X20	W6X20
		FOOTING	2'-0"X5'-6"	2'-0"X6'-0"	2'-0"X6'-6"	2'-0"X7'-6"

EXPOSURE C

HEIGHT ABOVE GRADE (A) (FT)	DISPLAY HEIGHT (FT)		DESIGN WIND VELOCITY	
			115 MPH	140 MPH
10'	3'-6"	COLUMN	W6X15	W6X15
		FOOTING	2'-0"X5'-6"	2'-0"X6'-6"
15'	3'-6"	COLUMN	W6X20	W6X20
		FOOTING	2'-0"X6'-6"	2'-0"X7'-6"

FOOTING DIMENSIONS = DIAMETER X DEPTH

REV 01	DATE: 01 APR 16	REMOVED MODEL NUMBERS TO MAKE DWG GENERIC		BY: KDD	
 THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF DAKTRONICS, INC. OR ITS WHOLLY OWNED SUBSIDIARIES. COPYRIGHT 2016 DAKTRONICS, INC. (USA)					
PROJECT: OUTDOOR LED SCOREBOARDS					
TITLE: INSTALLATION SPECS: 3'-6"X9' MODELS- 1 AD, 9' WIDE DISPLAY					
DATE: 15 MAY 14		DIM UNITS: INCHES [MILLIMETERS]		SHEET	REV
SCALE: 1/90		DO NOT SCALE DRAWING			01
DESIGN: TTASCHNER		JOB NO. P1192	FUNC - TYPE - SIZE R - 10 - A	1173106	
DRAWN: TTASCHNER					


NOTES:

1. FOOTING AND COLUMN SIZES ARE SUGGESTIONS ONLY, PROVIDED TO ASSIST WITH ESTIMATING INSTALLATION COSTS AND ARE NOT INTENDED FOR CONSTRUCTION PURPOSES. THE DESIGN MUST BE CERTIFIED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF THE INSTALLATION BEFORE THEY CAN BE USED FOR FABRICATION OR ERECTION.
2. INTERNATIONAL BUILDING CODE 2012 USED IN DESIGN OF COLUMNS AND FOOTINGS WITH, IMPORTANCE FACTOR=1, Kzt=1.0, Kd=0.85, G=0.85. SEISMIC DESIGN WAS NOT CONSIDERED.
3. FOOTING DIMENSIONS ARE BASED ON ASSUMED SOIL CLASS 4 (ALLOWABLE LATERAL BEARING PRESSURE OF 150 psf).
4. STRUCTURAL STEEL IS GRADE A992 (50 ksi) STEEL. CONCRETE SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2500 psi.
5. THE AVERAGE DISPLAY WEIGHT FOR A LAYOUT CAN NOT EXCEED 8 PSF.
6. DAKTRONICS INC. IS NOT RESPONSIBLE FOR STRUCTURES DESIGNED AND INSTALLED BY OTHERS.
7. LOCAL BUILDING OFFICIALS SHOULD BE CONTACTED TO DETERMINE THE WIND SPEED AND EXPOSURE CATEGORY FOR THE PROPOSED SIGN LOCATION. THE EXPOSURE CATEGORIES B AND C ARE DEFINED AS:

EXPOSURE B - URBAN AND SUBURBAN AREAS, WOODED AREAS, OR OTHER TERRAIN WITH NUMEROUS CLOSELY SPACED OBSTRUCTIONS HAVING THE SIZE OF SINGLE-FAMILY DWELLINGS OR LARGER. THESE CONDITIONS MUST PREVAIL FOR A DISTANCE FROM THE SIGN OF AT LEAST 2,600 ft OR 20 TIMES THE SIGN HEIGHT, WHICHEVER IS GREATER

EXPOSURE C - OPEN TERRAIN WITH SCATTERED OBSTRUCTIONS HAVING HEIGHTS GENERALLY LESS THAN 30 FT. THIS CATEGORY INCLUDES FLAT OPEN COUNTRY, GRASSLANDS, AND ALL WATER SURFACES IN HURRICANE PRONE REGIONS.

8. FOR SPECIFIC PRODUCT DETAILS ON WEIGHT, MOUNTING, ETC. REFER TO THE INDIVIDUAL PRODUCT SPECIFICATION SHEETS.



EXPOSURE_B

HEIGHT ABOVE GRADE (A) (FT)	DISPLAY HEIGHT (FT)		DESIGN WIND VELOCITY			
			115 MPH	130 MPH	150 MPH	170 MPH
10'	3'-6"	COLUMN	W6X15	W6X15	W6X15	W6X20
		FOOTING	2'-0"x5'-6"	2'-0"x6'-0"	2'-0"x6'-6"	2'-0"x7'-0"
15'	3'-6"	COLUMN	W6X20	W6X20	W6X20	W8X24
		FOOTING	2'-0"x6'-0"	2'-0"x6'-6"	2'-0"x7'-6"	2'-0"x8'-6"



EXPOSURE_C

HEIGHT ABOVE GRADE (A) (FT)	DISPLAY HEIGHT (FT)		DESIGN WIND VELOCITY	
			115 MPH	140 MPH
10'	3'-6"	COLUMN	W6X15	W6X20
		FOOTING	2'-0"x6'-6"	2'-0"x7'-0"
15'	3'-6"	COLUMN	W6X20	W8X24
		FOOTING	2'-0"x7'-0"	2'-0"x8'-0"



FOOTING DIMENSIONS = DIAMETER X DEPTH

REV 01	DATE: 01 APR 16	REMOVE MODEL NUMBERS TO MAKE DWG GENERIC	BY: KDD
		THIRD ANGLE PROJECTION	
THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF DAKTRONICS, INC. OR ITS WHOLLY OWNED SUBSIDIARIES. COPYRIGHT 2016 DAKTRONICS, INC. (USA)			
PROJECT: OUTDOOR LED SCOREBOARDS			
TITLE: INSTALLATION SPECS: 3'-6"X12' MODELS-2 ADS, 12' WIDE DISPLAY			
DATE: 15MAY14	DIM UNITS: INCHES [MILLIMETERS]	SHEET	REV
SCALE: 1=90	DO NOT SCALE DRAWING		01
DESIGN: TTASCHNER	JOB NO. P1192	FUNC - TYPE - SIZE R - 10 - A	1173107
DRAWN: TTASCHNER			

STANDARD SHEETMETAL SCOREBOARD/BACKLIT
AD PANEL MOUNTING METHOD



STANDARD NON-BACKLIT AD PANEL MOUNTING METHOD



QUALIFIED FOR SECTIONS UP TO 5' IN HEIGHT
USING RECOMMENDED STRUCTURE

ALLOWABLE CAPACITY PER EACH CLAMP:
SHEAR = 160 LBS
TENSION = 1376 LBS


SHEAR AND TENSION LOAD
DIRECTION ARE AS INDICATED ON
ROTATED VIEWS

- MOUNTING INSTRUCTIONS:**
1. LIFT THE FIRST SECTION OF THE DISPLAY INTO POSITION AGAINST I-BEAMS.
NOTE: IF THE DISPLAY IS MADE UP OF MULTIPLE SECTIONS ALWAYS INSTALL THE BOTTOM SECTION FIRST AND WORK UP.
 2. STARTING ON THE TOP OF THE SECTION BEING INSTALLED MARK AND DRILL 9/16\"

REV 02	DATE: 17 JUN 15	CHANGED TENSION CAPACITY TO 1376 LBS ADDED MINIMUM AND MAXIMUM FLANGE WIDTHS	BY: AMP
REV 01	DATE: 8 JAN 14	ADDED ALLOWABLE TENSION AND SHEAR CAPACITY DETAILS ADDED NON-BKLT AD PANEL MOUNTING DETAILS CHANGED DIMS TO B SIZE	BY: JAVA

PROJ: OUTDOOR SCOREBOARD		THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF DAKTRONICS, INC. COPYRIGHT 2014 DAKTRONICS, INC.	
TITLE: I-BEAM CLAMP MOUNTING, SHEET METAL ATTACHMENT		DATE: 17-JUN-15	
DESIGN: KSCHNABEL	DRAWN: KSCHNABEL		
SCALE: 1/8			
SHEET: 1 OF 1	REV: 02	JOB NO: P 1753	FUNC-TYPE-SIZE: E - 10 - B

1129110




MOUNTING INSTRUCTIONS:

1. USE THE MOUNTING CHANNEL TO DETERMINE WHICH HOLE COMBINATION SHOULD BE USED. BE SURE TO KEEP THE BOLT AS CLOSE TO THE BEAM AS POSSIBLE.
2. USING THE MOUNTING CHANNEL AS A TEMPLATE, DRILL 9/16" HOLES IN THE UPPER AND LOWER REAR FLANGE OF SCOREBOARDS WHERE THE SUPPORTS WILL GO.
3. PLACE SQUARE NUTS INSIDE CHANNEL AND THREAD BOLTS THROUGH.
4. LIFT SCOREBOARD INTO POSITION WITH BOLTS STILL IN PLACE.
5. PLACE MOUNTING ANGLES OVER EACH PAIR OF BOLTS AND SECURE WITH LOCK WASHERS AND HEX NUTS.
6. WHEN SCOREBOARD IS ADJUSTED TO FINAL DESIRED POSITION, TIGHTEN HEX NUTS FIRMLY.

 DAKTRONICS, INC. BROOKINGS, SD 57006 DO NOT SCALE DRAWING		THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESSED WRITTEN CONSENT OF DAKTRONICS, INC. COPYRIGHT 2013 DAKTRONICS, INC.	
PROJ: OUTDOOR SHEET METAL SCOREBOARDS			
TITLE: SCOREBOARD MOUNTING			
DESIGN: KDRAGT		DRAWN: KDRAGT	
SCALE: 1=8		DATE: 14 MAR 13	
SHEET	REV	JOB NO:	FUNC - TYPE - SIZE
00	00	P1753	E - 10 - A
1130246			1130246

MS-2025-R/A/W



FRONT VIEW

NOTES:

3 = DRIVER CONNECTOR
WIRED TO THAT DIGIT

18" = DIGIT SIZE

A1 = DRIVER NUMBER

							DAKTRONICS, INC. BROOKINGS, SD 57006		THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESSED WRITTEN CONSENT OF DAKTRONICS, INC. COPYRIGHT 2013 DAKTRONICS, INC.				
					DO NOT SCALE DRAWING								
					PROJ:OUTDOOR SHEETMETAL SCOREBOARDS								
					TITLE:COMPONENT LOCATION; MS-2025-101X-R/A/W								
REV	DATE:	PER	BY:		DESIGN:KDRAGT			DRAWN:KDRAGT			DATE: 20 FEB 13		
02	17 AUG 20	CN-108201 REMOVED LABELS TO MOVE TO NEW STANDARD	TAN		SCALE: 1=20								
REV	DATE:	PER	BY:		SHEET		REV	JOB NO:		FUNC-TYPE-SIZE		1128100	
01	03 MAR 15	EC-17119, ADDED SIGNAL OPTION NOTE AND REMOVED DETAIL VIEW	ZSW				02	P 1753		E - 10 - A			